Electrotype Copy No. 1 by G. Mathiot U.S.C.S

ENTRANCE TO CHESAPEAKE BAY

Scale 100,000

Statute Miles

Nautical Miles

TIDES

Corrected Establishment, Old Point Comfort	VIII^h XVII^m
Rise of Highest Tide observed above the plane of reference	4.8 Ft.
Fall of Lowest Tide ..... do ..... below ..... do ..... do	1.7 -
Fall of Mean Low Water of Spring Tides below ..... do	0.5 -
Height of Mean Low Water of Neap Tides above ..... do	0.3 -
Mean Rise and Fall of Tides	2.5 -
Mean ..... do ..... of Spring Tides	3.0 -
Mean ..... do ..... of Neap Tides	2.0 -
Mean Duration of Rise { Reckoning from the middle of one	12^h 25^m
Mean ..... do ..... of Fall } stand to the middle of the next	0^h 23^m
Mean ..... do ..... of Stand	0^h 14^m

Mean Rise and Fall of Tides at Metomkin Inlet 3.5 ft. — at Wachapreague Inlet 3.5 ft. - and at Ship Shoal Inlet 3.1 ft.

Abbreviations used in the bottoms of this Chart

Materials in Capitals	Colors or Shades two small letters	Other qualities three small letters
M. for Mud	bk. for black	hrd. for hard
S. - Sand	wh. - white	sft. - soft
G. - Gravel	rd. - red	fne. - fine
Sh. - Shells	yl. - yellow	crs. - coarse
P. - Pebbles	gy. - grey	brk. - broken
Sp. - Specks	bu. - blue	sml. - small
	dk. - dark	
	lt. - light	

Note. *The principal materials and their qualities are represented by larger letters than the subsidiary.*

In the description of buoys P.S. signifies perpendicular stripes - B. black and R. red.

CURRENTS

No.	Station	1st Quarter Set	1st Quarter Drift	Maximum Set	Maximum Drift	3d Quarter Set	3d Quarter Drift	Flood or Ebb
1	Near Shark Shoal	N.13°W.	0.1	West.	0.2	N.16°W.	0.1	Flood
2	East of Middle Ground	N.13°E.	0.2	N.26°E.	0.4	S.26°E.	0.2	Ebb
3	1½ mile N. of Cape Henry Lt. Ho.	N.24°W.	0.3	N.39°W.	0.5	N.35°W.	0.3	Flood
		S.24°E.	0.3	S.15°E.	0.7	S.6°E.	0.5	Ebb
4	Lynn Haven Roads	N.24°W.	0.5	N.39°W.	0.8	N.50°W.	0.7	Flood
		S.24°E.	0.5	S.15°E.	0.7	S.6°E.	0.5	Ebb
5	Between Tail of Horse Shoe & Horse Shoe	West	0.5	N.71°W.	1.1	N.24°W.	0.6	Flood
		N.73°E.	0.5	East	1.0	S.77°E.	0.6	Ebb
6	Nd. & Ed. of Light Boat	N.73°W.	0.8	N.55°W.	1.9	N.47°W.	0.9	Flood
		N.78°E.	0.8	S.59°E.	1.5	South	0.7	Ebb
7	Between Old Pt. & Rip Raps	N.54°W.	0.6	N.62°W.	0.9	N.54°W.	0.6	Flood
		S.54°E.	0.6	S.62°E.	1.3	East	1.0	Ebb
8	East of Back River Lt. Ho.	N.73°W.	0.6	S.76°W.	1.0	S.74°W.	1.2	Flood
		S.60°E.	1.3	S.43°E.	1.7	S.81°E.	0.9	Ebb
9	Tail of York Spit	N.24°W.	0.5	N.39°W.	0.8	N.50°W.	0.7	Flood
		S.24°E.	0.5	South	0.8	S.15°E.	0.5	Ebb
10	Channel East of York Spit	N.45°W.	0.3	N.71°E.	0.9	S.74°E.	0.5	Flood
		S.9°E.	0.8	S.26°E.	1.2	S.32°E.	0.5	Ebb

Note. The observations were made as far as practicable when the influence of the wind was small. The bearings are True. The drifts are in Nautical miles, shown on the chart by figures near the ends of the current arrows.

SAILING DIRECTIONS

To enter Chesapeake Bay by Cape Henry Channel. *Bring Cape Henry Lt.Ho. to bear from W by S. to W.N.W. and stand for it. Between these bearings there is not less than 54 fms. The channel between Cape Henry and the Middle Ground is about 4¾ miles wide. Large class vessels working in or out must beware of the 3¼ fms. shoal lying 3¼ miles Northward & Eastward of Cape Henry Lt. Ho. Keep the lead going after striking 12 fms. The beach from the Lt. Ho. Southerly must not be approached nearer than a mile. When inshore to the Southward & Eastward, standing to the Northward, till Willoughby's Pt. woods range with or open to the Northward of Cape Henry, deepens the water into Cape Henry Channel, and the bottom changes from hard to sticky and soft. Approaching from the Northward & Eastward, inshore, after passing Smith's Id. Lt. Ho. keep it well open with the woods to the Southward, keeping in not less than 3¼ fms to avoid Nautilus Shoal. Vessels making the land to the Southward of Cape Henry during a strong North Wester should not approach it nearer than 8 miles, as the ebb tide then sets strong to the Southward, along shore. Stretch well off on the Port tacks, and bring Cape Henry to bear West. The woods of Smith's Id. appear broken and uneven from a distance seaward, when bearing from W.N.W. to W.S.W. with other bearings they appear even and solid.*

If bound into Hampton Roads, *bring Cape Henry Lt. Ho. to bear S. dist. ¼ miles and steer W.N.W.¼W keeping Willoughby's Lt. Boat a little on the Port bow. If the tide is running flood, steer 1 point more to the Southward. If ebb 1 point more to the Northward. As Old Pt. Lt. Ho. opens to the Northward of the Lt. Boat change course gradually for the Lt. Ho. leaving the Lt. Boat two or three ships lengths to the Southward. When the E. end of Rip Raps is on with Sewall's Pt. steer midway between the Rip Raps and Old. Pt. Lt. Ho for Hampton Roads, and anchor in from 7 to 10 fms. Old Pt. Lt. Ho. bearing from N.E. ½ N. to N.E.½E. dist. one two or three miles. Moor with open hawse to the Northward & Eastward. Keeping Old. Pt. Lt. Ho a little open to the Southward of the Lt. Boat clears the Tail of the Horse Shoe, and when within three or four miles of the Lt. Boat keeping it in range with the Lt. Ho. carries clear of the Southern edge of the Horse Shoe. When beating in the neighborhood of the Lt. Boat beware of the Thimble on the opposite side of the channel, bearing from N.N. by E. & N.N.E. from Old Pt. Lt. Ho. E. by N. and Old Pt. Comfort Sand Hill East.*

If bound to Baltimore *bring Cape Henry Lt. Ho. to bear S.S.E.¼E. dist. 2 miles, or just shut in the beach to the Southward of it. Steer N.E.¼E.¼N. till Rock R. Lt. Ho. bears S.S.W. When a N.E. course will clear Wolf Trap Lt. Boat. The soundings decrease gradually in approaching the Horse Shoe, but change suddenly on the W. side of the Middle Ground. If bound into York R. the lead and compass must be the principal guides. Keep the Port hand going in, as on that side the soundings decrease gradually, but it is steep to on the side of York Spit.*

To enter by the N. Channel. *It is better for steamers than sailing vessels as the ebb tide runs strong and there are cross tides. Bring Smiths Id. Lt. Ho. to bear N. dist. 3¼ miles and the W. end of Smith's Id. N.W.¼W. dist. 3 miles being in 3 fms. water. Steer W.¼ S. keeping the breakers on the Starbd. hand from ¼ to a mile dist. This course leads about midway between the Isaacs Breakers and Nautilus Shoal crossing 15 ft. When Guy's Pt. (the Northernmost point of trees in sight) just opens to the Westd. of the N. end of Fisherman's Id. haul to the Northward, and steer with the Pt. a little on the starbd. bow (passing Fisherman's Id. ¼ mile dist. on the Starbd. hand) till abreast of Butler's Bluff, when haul to the Northward & Westward. Keep the lead going while passing through. There is a shoal of 11 ft. on the range of E. end of Fisherman's Id. on with W. end of the Isaacs. Entering N. Channel from the Southward, and Westward, to clear the S. end of the Inner Middle, keep Richardson's House (the nearest to Cape Charles with a poplar by it) over and to the Eastward of the N. end of Fisherman's Id. To avoid the North end of the Inner Middle keep the S. W. end of Smith's Id. shut in with the point of woods at Cape Charles.*

Coming down Chesapeake Bay bound into Hampton Roads to avoid the Thimble and other shoal water on the Horse Shoe, bring Willoughby's Lt. Boat and the Rip Raps in range. If bound from Hampton Roads to James R. keeping the S. E. angle of Ft. Monroe just open to the Southward of Old Pt. Lt. Ho. clears Hampton Bar, and the shoal water further up Willoughby's Point, just shut in to the Southward of Sewall's Pt. clears the Southern edge of Newport News Middle Ground.

Bound up Elizabeth R. to Norfolk, keep Willoughby's Lt. Boat a little open to the Northward of the Rip Raps to clear the shoal between the Rip Raps and Sewall's Pt. keep in not less than 44 fms. as it is steep to. To clear Bush's Bluff Shoal keep Old Pt. Lt. Ho. a little open to the Westward of Sewall's Pt. till abreast of Bush's Bluff Woods, when haul up for the Lt. Boat, leaving it on the Starbd. hand. A mark at night for having cleared the shoal is when abreast of the broad clear opening in the woods just to the Southward of it.

DANGERS

The attention of mariners is particularly directed to the position, extent, and depth of water on Smith's Id. and Shark Shoals and the Middle Ground, as shown by the chart. There is a shoal with 16 Ft. E.N.E. from False Cape dist. 12 miles with 54 fms. inside.

The Middle Ground *commences about 6 miles N.E. ½ E. from Cape Henry Lt. Ho. gradually shoaling from seaward to 4 fms. and extending to the Westward and Northward, & Eastward, up the Bay 15 miles. It is very steep to on the Western side, suddenly shoaling from 7 and 6 fms. to 18 and 16 ft.*

The Horse Shoe *is a triangular shaped shoal making out from the shore between Back R. and Old Pt. The Eastern extremity called the Tail of the Horse Shoe, is 3¾ miles from Old Pt. Lt. Ho. There is from 9 ft. to 3¾ fms. on the shoal.*

Willoughby's Bank *is a narrow shoal off Willoughby's Pt. and the Rip Raps, 2¼ miles long, extending E.N.E. and W.S.W. with from 6 to 13 ft. on it. There is a channel of 18 ft. between it and the S. shore.*

The Thimble *is a small but dangerous shoal with 10 and 11 ft. on the S. edge of the Horse Shoe 2¼ miles E. of Old Pt. Sand Hill. There are 6 fms. close to on the S. side. A red buoy with Thimble on it marks the shoal.*

York Spit *is about a mile in width with from 3 to 18 ft. on it, extending out from between Mob Jack Bay and York R. At 5¼ miles from land, there is a spot with 9 ft. at 6 miles it deepens beyond 5 fms.*

New Pt. Shoal *4 miles S.E. of New Pt. Comfort Lt. Ho. with 16 ft. on it is ¾ of a mile long, and 1 wide, extending E.N.E. and W.S.W.*

The Inner Middle Shoals *near Cape Charles are most deceptive and dangerous. They are 4¼ miles long and from one to 1½ wide, the depth varying from 3 to 12 ft. It breaks on the shoalest part only with a swell setting from seaward.*

Nautilus Shoal *lies 2 miles S. by E.¼E. from the E. end of the Isaacs. The point of woods at Cape Charles on with Guy's Pt. is a range for it. There is 18 ft water on it.*

NOTE

As the variation of the Compass is less than a quarter of a point in the lower part of the Bay, the courses and bearings given are True. The distances are in Nautical miles. The soundings are expressed in feet to 18 ft, or within the dotted surface, beyond it in fms. and show the depth at mean low water - the plane of reference. The characteristic soundings only are given on the chart, they are selected from the numerous soundings taken in the survey so as to represent the figure of the bottom.

Name and Locality	Latitude	Longitude West from Greenwich, Observatory. In. arc	In. time
Hog Island Light House	37° 23' 17"	75° 41' 35"	5h 02m 46s3
Smiths Island ..... do ..... do	37° 07' 48"	75° 52' 12"	5h 03m 28s8
Cape Henry ..... do ..... do	36° 55' 29"	76° 00' 12"	5h 04m 00s8

The Triangulation was executed in	*1850-51 & 52*
The Topography ..... do ..... do ..... in	*1852-53 & 54*
The Hydrography ..... do ..... do ..... in	*1852-53 & 54*
Variation of the Magnetic Needle at Sand Shoal Inlet in Jan. 1854	*2° 06' W.*

PRELIMINARY CHART
OF PART OF
THE SEA COAST OF VIRGINIA
AND
ENTRANCE TO CHESAPEAKE BAY

From a Trigonometrical Survey

under the direction of A.D. BACHE Superintendent of the

SURVEY OF THE COAST OF THE UNITED STATES

Triangulation by JOHN FARLEY Assistant

Topography by G. D. WISE Assist. & J. SEIB Sub. Assistant

Hydrography by the Party under the command of

Lieut. J. J. ALMY U.S.N. Assist.

Scale 200,000

1855

Price 20 cents

Verified
W^m W. Latham, Capt. of Eng^rs
Asst. C.S. In charge of Office.

Statute Miles

Nautical Miles

Red^d & Dr^wn by L.D. Williams, A. Shoepf, & A. Balbach.

Engd by E. Yeager, H.S. Barnard, A. Petersen & App. R.F. Bartle

RAREBK VK 982 .C5 B3 1861 Chart G

NOAA CENTRAL LIBRARY 3 8398 1010 3066 0